

SECTION 13 – STREET-LEGAL ALL TERRAIN VEHICLE

An all-terrain vehicle that is a Type I or Utility Type Vehicle 'UTV' may be inspected and registered as a Street-legal ATV. These ATV types are defined as:

"All-terrain Type I Vehicle" means any motor vehicle 52 inches or less in width, having an unladen dry weight of 1,500 pounds or less, traveling on three or more low pressure tires, having a seat designed to be straddled by the operator, and designed for or capable of travel over unimproved terrain.

"Utility Type Vehicle" means any recreational vehicle designed for and capable of travel over unimproved terrain: traveling on four or more tires, having a width of 30 to 70 inches, having an unladen dry weight of 2,200 pounds or less, having a seat height of 25 to 40 inches when measured at the forward edge of the seat bottom, and having side by side seating with a steering wheel for control. "Utility type vehicle" does not include an all-terrain type I vehicle, an all-terrain type II vehicle, a motorcycle or a snowmobile.

A. Street-legal all-terrain vehicles

1. All-terrain vehicles may be inspected provided that they have been modified to be street legal. They shall be equipped with the following items, which shall comply with the regulations of the department (41-6a-1509).
 - a. One or more headlamps that meet the requirements of U.C.A. 41-6a-1603.
 - b. One or more tail lamps.
 - c. A tail lamp or other lamp constructed and placed to illuminate the registration plate with a white light.
 - d. One or more red reflectors on the rear.
 - e. One or more stop lamps on the rear.
 - f. Amber or red electric turn signals, one on each side of the front and rear. (Amber for the front and red for the rear)
 - g. A braking system, other than a parking brake, that meets the requirements of U.C.A. 41-6a-1623.
 - h. A horn or other warning device that meets the requirements of U.C.A. 41-6a-1625.
 - i. A muffler and emission control system that meets the requirements of U.C.A. 41-6a-1626.
 - j. Rearview mirrors on the right and left side of the driver in accordance with U.C.A. 41-6a-627. (A type I ATV requires only a left side mirror and a 'UTV' requires both a left side and right side mirror.)
 - k. A windshield, unless the operator wears eye protection while operating the vehicle.
 - l. A speedometer, illuminated for nighttime operations.

STREET-LEGAL ALL TERRAIN VEHICLE – Continued

- m. Vehicles designed by the manufacturer for carrying one or more passengers, a seat designed for passengers, including a footrest and handhold for each passenger.
 - n. Vehicles with side by side seating, seatbelts for each vehicle occupant.
 - o. Must not be less than 30 inches in width or exceed 70 inches in width. Measurement must be taken at the widest point of the vehicle, including tires.
 - p. Drivers seat must not be less than 25 inches in height or exceed 40 inches in height. This measurement must be made from the ground to the top of the forward edge of the seating position when measured on a flat level surface.
 - q. The tire tread depth must be at least 2/32 of an inch and the tires must not exceed 26 inches in height or be larger than the ATV manufacturer made available for the ATV model.
1. **REJECT** when:
- a) Any of the above requirements are not met.



'Utility Type Vehicle'



'Utility Type Vehicle'



'Utility Type Vehicle'



All-terrain Type I Vehicle

Note: Sandrails, Rock Crawlers, and go-carts will not be allowed to be inspected and registered as a street-legal ATV.